

ADINOL-DM

DECLARATION OF PERFORMANCE

Declaration number: **ADINOL-DM / 1612-01**

| | |
|---|---|
| 1.Unique identification code of the product type | ADINOL-DM |
| 2.Intended use/uses | Water resisting admixture for concrete |
| 3.Manufacturer | <i>ISOMAT S.A</i> 17th Km Thessaloniki-Ag. Athanasios 57003 Ag. Athanasios, Greece |
| 4.Authorised representative | <i>ISOMAT D.O.O.</i> Prhovacka bb, 22310, Šimanovci, Serbia <i>ISOMAT ROMANIA SRL</i> Str. Islazului Nr.1-5, Pantelimon, 077145 Jud. Ilfov, Romania <i>ISOMAT INTERNATIONAL E.O.O.D.</i> Botevgradsko Shosse No.348. Sofia, Bulgaria <i>ISOMAT GRADBENI MATERIALI D.O.O.</i> Cvetkova ulica 2 9000 Murska Sobota, Slovenia <i>ISOMAT YAPI KIMYASALLARI VE TIC.LTD.STI.</i> <i>ISTANBUL</i> IOSB S. Demirel Bulvan, Heskop Is Modern San. Sit., J Blok Zemin Kat No 20, Basaksehir <i>ООО «ИЗОМАТ»</i> 17, Nauchniy proezd, building 15-3 117246, MOSCOW, Russian Federation <i>ISOMAT DEUTSCHLAND GMBH</i> Karl-Wirth-Strasse 14 D-76694 Forst,Germany |
| 5.System/s of AVCP | System 2+ (for uses in buildings and civil engineering works) |

| | |
|--|--------------------------------|
| 6a.Harmonised standard | EN 934-2:2009+A1:2012 |
| Notified body/ies | TÜV AUSTRIA HELLAS, NB 0906 |
| 6b.European Assessment Document | Not relevant |
| European Technical Assessment | Not relevant |
| Technical Assessment body | Not relevant |
| Notified body/ies | Not relevant |

| 7.Declared performance/s | | | |
|--|---|--------------------|---|
| Essential characteristics | Performance | Test Method | Harmonized Technical Specification |
| Capillary absorption | Tested for 7 days after 7 days curing: test mix \leq 50% by mass of control mix Tested for 28 days after 90 days curing: test mix \leq 60 % by mass of control mix | EN 480-5 | EN 934-2:2009 +A1:2012 T.9 |
| Compressive strength at 28 days | Test mix \geq 85% of control mix | EN 12390-3 | |
| Air content in fresh concrete | Test mix \leq 2% (by volume) above control mix | EN 12350-7 | |
| Chloride ion content | \leq 0,1% by mass | EN 480-10 | |
| Alkali content | \leq 4,0% by mass | EN 480-12 | |
| Corrosion behaviour | Contains the following components from EN 934-1: 2008, Annex A.1 | EN 480-14 | |
| Dangerous substances | Compliance | | |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above:

Signed for and on behalf of the manufacturer by:



Konstantinos Iliopoulos
Quality Manager



Georgios Syriopoulos
Certifications & Specifications Manager

Agios Athanasios 23 / 10 / 2024

CE MARKING



0906

ISOMAT S.A.
17th km Thessaloniki – Ag. Athanasios
P.O. BOX 1043, 570 03 Ag Athanasios, Greece

18

0906-CPR-02412007/01

EN 934-2:2009+A1:2012

DoP No.: ADINOL-DM/1612-01

ADINOL-DM

Water resisting admixture for concrete
EN 934-2: T.9

Max chloride content: chloride free

Max alkali content: $\leq 4,0$ % by weight

Corrosion behaviour: contains components only
from EN 934-1:2008, Annex A.1

Dangerous substances: compliance



Visit our website:
www.isomat.eu

ISOMAT S.A.
BUILDING CHEMICALS,
MORTARS & PAINTS
export@isomat.eu | www.isomat.eu

HEADQUARTERS
THESSALONIKI, GREECE
17th km Thessaloniki - Ag. Athanasios Road
P. O. BOX 1043, 570 03 Ag. Athanasios
T: +30 2310 576 000



CERTIFIED COMPANY