

# STUCCOCRET-PLUS

## DECLARATION OF PERFORMANCE

Declaration number: **STUCCOCRET-PLUS / 1224-04**

<b>1.Unique identification code of the product type</b>	STUCCOCRET PLUS
<b>2.Intended use/uses</b>	General purpose mortar polymer modified for smoothing interior surfaces (GP, CS II)
<b>3.Manufacturer</b>	<i>ISOMAT S.A</i> 17th Km Thessaloniki-Ag. Athanasios 57003 Ag. Athanasios, Greece
<b>4.Authorised representative</b>	<i>ISOMAT D.O.O.</i> Prhovacka bb, 22310, Šimanovci, Serbia  <i>ISOMAT ROMANIA SRL</i> Str. Islazului Nr.1-5, Pantelimon, 077145 Jud. Ilfov, Romania  <i>ISOMAT INTERNATIONAL E.O.O.D.</i> Botevgradsko Shosse No.348. Sofia, Bulgaria  <i>ISOMAT GRADBENI MATERIALI D.O.O.</i> Cvetkova ulica 2 9000 Murska Sobota, Slovenia  <i>ISOMAT YAPI KIMYASALLARI VE TIC.LTD.STI.</i> ISTANBUL IOSB S. Demirel Bulvan, Heskop Is Modern San. Sit., J Blok Zemin Kat No 20, Basaksehir  <i>ООО «ИЗОМАТ»</i> 17, Nauchniy proezd, building 15-3 117246, MOSCOW, Russian Federation  <i>ISOMAT DEUTSCHLAND GMBH</i> Karl-Wirth-Strasse 14 D-76694 Forst,Germany
<b>5.System/s of AVCP</b>	System 4

<b>6a.Harmonised standard</b>	EN 998-1:2016
<b>Notified body/ies</b>	Not relevant
<b>6b.European Assessment Document</b>	Not relevant
<b>European Technical Assessment</b>	Not relevant
<b>Technical Assessment body</b>	Not relevant
<b>Notified body/ies</b>	Not relevant

<b>7.Declared performance/s</b>			
<b>Essential characteristics</b>	<b>Performance</b>	<b>Test Method</b>	<b>Harmonized Technical Specification</b>
<b>Reaction to fire</b>	class A1	EN 13501-1	<b>EN 998-1:2016</b>
<b>Capillary water absorption</b>	W0	EN 1015-18	
<b>Water vapour permeability</b>	$\mu$ :21	EN 1015-19	
<b>Adhesion</b>	$\geq 0,5$ N/mm <sup>2</sup> - FP:A	EN 1015-12	
<b>Thermal conductivity <math>\lambda_{10 dry}</math></b>	0,24 W/mK (tabulated)	EN 1745	
<b>Durability</b>	evaluation based on provisions valid in the intended place of use of the mortar		
<b>Dangerous substances</b>	complies with paragraph 5.3.4		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above:

Signed for and on behalf of the manufacturer by:



**Konstantinos Iliopoulos**  
Quality Manager



**Georgios Syriopoulos**  
Certifications & Specifications Manager

**Agios Athanasios 25 / 07 / 2022**

## CE MARKING



**ISOMAT S.A.**

17<sup>th</sup> km Thessaloniki – Ag. Athanasios  
P.O. BOX 1043, 570 03 Ag. Athanasios, Greece

12

**EN 998-1**

**General purpose plastering mortar (GP)  
for internal use**

DoP No.: STUCCOCRET-PLUS/1224-04

**Reaction to fire:** Class A1

**Adhesion:** 0.5 N/mm<sup>2</sup> – **FP:** A

**Water absorption:** W0

**Water vapor diffusion coeff.:**  $\mu$  21

**Thermal conductivity:** ( $\lambda_{10,dry}$ ) 0.24 W/mK

**Durability** (against freeze/thaw): evaluation  
based on provisions valid in the intended place of  
use of the mortar



Visit our website:

**[www.isomat.eu](http://www.isomat.eu)**

**ISOMAT S.A.**  
**BUILDING CHEMICALS,**  
**MORTARS & PAINTS**  
export@isomat.eu | [www.isomat.eu](http://www.isomat.eu)

---

**HEADQUARTERS**  
**THESSALONIKI, GREECE**  
17th km Thessaloniki - Ag. Athanasios Road  
P. O. BOX 1043, 570 03 Ag. Athanasios  
**T: +30 2310 576 000**



CERTIFIED COMPANY