

STUCCOCRET

DECLARATION OF PERFORMANCE

Declaration number: **STUCCOCRET / 1225-03**

1.Unique identification code of the product type	STUCCOCRET
2.Intended use/uses	General purpose mortar for smoothing interior surfaces (GP, CS II)
3.Manufacturer	<i>ISOMAT S.A</i> 17th Km Thessaloniki-Ag. Athanasios 57003 Ag. Athanasios, Greece
4.Authorised representative	<i>ISOMAT D.O.O.</i> Prhovacka bb, 22310, Šimanovci, Serbia <i>ISOMAT ROMANIA SRL</i> Str. Islazului Nr.1-5, Pantelimon, 077145 Jud. Ilfov, Romania <i>ISOMAT INTERNATIONAL E.O.O.D.</i> Botevgradsko Shosse No.348. Sofia, Bulgaria <i>ISOMAT GRADBENI MATERIALI D.O.O.</i> Cvetkova ulica 2 9000 Murska Sobota, Slovenia <i>ISOMAT YAPI KIMYASALLARI VE TIC.LTD.STI.</i> ISTANBUL IOSB S. Demirel Bulvan, Heskop Is Modern San. Sit., J Blok Zemin Kat No 20, Basaksehir <i>ООО «ИЗОМАТ»</i> 17, Nauchniy proezd, building 15-3 117246, MOSCOW, Russian Federation <i>ISOMAT DEUTSCHLAND GMBH</i> Karl-Wirth-Strasse 14 D-76694 Forst,Germany
5.System/s of AVCP	System 4

6a.Harmonised standard	EN 998-1:2016
Notified body/ies	Not relevant
6b.European Assessment Document	Not relevant
European Technical Assessment	Not relevant
Technical Assessment body	Not relevant
Notified body/ies	Not relevant

7.Declared performance/s			
Essential characteristics	Performance	Test Method	Harmonized Technical Specification
Reaction to fire	class A1	EN 13501-1	EN 998-1:2016
Capillary water absorption	W0	EN 1015-18	
Water vapour permeability	μ :20	EN 1015-19	
Adhesion	$\geq 0,5$ N/mm ² - FP:A	EN 1015-12	
Thermal conductivity $\lambda_{10 dry}$	0,35 W/mK (tabulated)	EN 1745	
Durability	evaluation based on provisions valid in the intended place of use of the mortar		
Dangerous substances	complies with paragraph 5.3.4		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above:

Signed for and on behalf of the manufacturer by:



Konstantinos Iliopoulos
Quality Manager



Georgios Syriopoulos
Certifications & Specifications Manager

Agios Athanasios 25 / 07 / 2022

CE MARKING



ISOMAT S.A.

17th km Thessaloniki – Ag. Athanasios
P.O. BOX 1043, 570 03 Ag. Athanasios, Greece

10

EN 998-1

**General purpose plastering mortar (GP)
for internal use**

DoP No.: STUCCOCRET/1225-03

Reaction to fire: Class A1

Adhesion: 0.5 N/mm² – **FP:** A

Water absorption: W0

Water vapor diffusion coeff.: μ 20

Thermal conductivity: ($\lambda_{10,dry}$) 0.35 W/mK

Durability (against freeze/thaw): evaluation based on provisions valid in the intended place of use of the mortar



Visit our website:
www.isomat.eu

ISOMAT S.A.
BUILDING CHEMICALS,
MORTARS & PAINTS
export@isomat.eu | www.isomat.eu

HEADQUARTERS
THESSALONIKI, GREECE
17th km Thessaloniki - Ag. Athanasios Road
P. O. BOX 1043, 570 03 Ag. Athanasios
T: +30 2310 576 000



CERTIFIED COMPANY