

## Technical Datasheet

# **MULTIFILL-EPOXY CLEANER**

# Cleaning agent for epoxy grout residue

## **Description**

Special gel cleaner containing a mixture of solvents.

#### Fields of application

MULTIFILL-EPOXY CLEANER is used to remove residue of hardened epoxy grout (e.g. MULTIFILL-EPOXY THIXO) from tile surfaces, due to inadequate cleaning of the grout during its application. Suitable for horizontal and vertical surfaces.

#### **Technical data**

Form: gel

Color: transparent

pH: 7.5

Density: 1.05 kg/l Application temperature: 5-35°C Dissolution time of residue: 1-8 h

#### **Directions for use**

MULTIFILL-EPOXY CLEANER is applied undiluted with a brush or trowel on the hardened residue of the epoxy grout and is then left to act, until it has softened the residue. This usually takes 1-8 hours, depending on the size of the residue. Finally, the residue is removed with a metal trowel and the surface is thoroughly rinsed with water. The procedure can be repeated, if necessary.

#### Consumption

Depending on the size of the residue that needs to be removed.

#### **Packaging**

MULTIFILL-EPOXY CLEANER is available in 0.75 I containers.

#### **Storage**


24 months from production date, in places protected from high temperatures and frost.

#### Remarks

- Consult the safety instructions written on the container before use.
- Protect surfaces that are sensitive to solvents from coming to direct contact with the cleaning agent (e.g. plastics).
- Before applying the product on polished tiles, marble or natural stone, try it first to make sure it does not change their appearance.
- Avoid contact of the cleaning agent with the tile joints, as it might damage the epoxy grout already used in the joints, in the same way it removes the grout residue from the tiles.
- MULTIFILL-EPOXY **CLEANER** highly flammable. Smoking is strictly prohibited during application.

ISOMAT S.A. **BUILDING CHEMICALS, MORTARS & PAINTS** HEADQUARTERS - THESSALONIKI, GREECE 17th km Thessaloniki - Ag. Athanasios Road P.O. BOX 1043, 570 03 Ag. Athanasios, Greece

www.isomat.eu e-mail: support@isomat.eu



T+30 2310 576000

