

## Technical Datasheet

# SILICONE-SPRAY

## Silicone spray lubricant

### Description

SILICONE-SPRAY is a high-quality silicone spray with 70% of silicones. It can be used on all types of surfaces. It provides durable protection.

- Suitable for use on plastic and metals
- Improved lubricating properties at high temperatures
- Excellent penetrating properties.
- Odorless
- Colorless
- No other additives

### Fields of application

- Usually used on metals, plastic and most other impervious surfaces. Particularly useful in the automotive market for lubrication of locks, hinges, door rubbers, window channels, antennas, battery terminals and so-called squeaky locations.
- Not for use in areas to be painted and in areas where corrosion protection is needed.

### Technical data

Material:	silicones
Color:	transparent
Specific gravity:	0.810-0.830
Viscosity:	slightly sticky liquid
Not volatile % m/m:	30-40
Active content:	5-10
Flammability:	highly ignitable, flash point below -20°C

Continuous  
operating temperature: 200°C

Intermittent  
operating temperature: 250°C

Self-ignition  
temperature: 250°C  
(DIN 51794)

Explosion limits,  
Vol % lower: 1.1  
(DIN 51649)

### Directions for use

Shake well before use. Spray directly on the surface from a distance of 20 to 30 cm.

### Packaging

Spray can 400 ml.

### Shelf life – Storage

24 months from production date if stored in cool, well-ventilated spaces, protected from direct sunlight and high temperatures.

**ISOMAT S.A.**  
BUILDING CHEMICALS, MORTARS & PAINTS  
**HEADQUARTERS – THESSALONIKI, GREECE**  
17<sup>th</sup> km Thessaloniki – Ag. Athanasios Road  
P.O. BOX 1043, 570 03 Ag. Athanasios, Greece  
T +30 2310 576000  
**www.isomat.eu e-mail: support@isomat.eu**